


Physical Dimensions

Entire top of module is conformal coated with Humiseal 1B31 or equivalent.

3M 468MP peel & stick tape on back of module, clean heatsink surface with isopropyl alcohol.



0.63" Nominal PCB thickness

Tolerances:
0.X ± 0.05
0.XX ± 0.005

Ts measurement point is cathode of center LED.

3" nominal length leads, 22 AWG stranded, strip ends 0.063", red (+), black (-).
CCT/CRI or color silkscreened on top of PCB, examples: "27K/80", "TFA", "RED".

Table 1, Performance Characteristics at 25°C

Data from laboratory test measurements, actual results may vary.

Part Number	Typical CCT/DWL (Kelvin/nm)	Min CRI	Max Current (ADC)	Typical VF (VDC)	Typical Power (WDC)	Typical Lumens	Typical Efficacy (DC LPW)
BB03AB-18-70-01	1800	70	0.45	8.7	3.9	456	117
BB03AB-20-70-01	2000	70	0.45	8.7	3.9	501	128
BB03AB-22-80-01	2200	80	0.45	8.7	3.9	503	129
BB03AB-25-80-01	2500	80	0.45	8.7	3.9	520	133
BB03AB-27-80-01	2700	80	0.45	8.7	3.9	569	145
BB03AB-30-80-01	3000	80	0.45	8.7	3.9	580	148
BB03AB-35-80-01	3500	80	0.45	8.7	3.9	591	151
BB03AB-40-80-01	4000	80	0.45	8.7	3.9	612	156
BB03AB-50-80-01	5000	80	0.45	8.7	3.9	617	158
BB03AB-65-80-01	6500	80	0.45	8.7	3.9	615	157
BB03AB-TFA-01	595	n/a	0.35	6.6	2.3	235	102
BB03AB-RED-01	622	n/a	0.35	6.6	2.3	218	94
BB03AB-GREEN-01	527	n/a	0.35	10.2	3.6	360	101
BB03AB-BLUE-01	470	n/a	0.35	8.8	3.1	111	36

Options and Packing

90CRI minimum versions on special order, 83% of 80CRI lumens.

Manufactured in groups of (242) unit(s) and packaged in ESD bags with SKU and lot information.

Warranty

5-Year limited warranty in accordance with published warranty conditions. Product must be used with compatible components (modules, drivers, engines and/or accessories) and no maximum ratings (such as Ts) shall be exceeded during any operating conditions of the system. If product is used with other manufacturer's product, compatibility must be recognized in writing by Forflux.

Forflux owns the following United States patents of which may be applicable to the design or manufacture of this product: 6712486, 6578986, 6846093, 7114831, 7306353, 7102172, 7108396, 7329024, 7387406, 7582911, 7649327, 8926145, 8729810. Additional granted patents, patents pending, and other IP protection rights may apply.